BUSINESS FORM ESTIMATION





ALES REPRESENTATIVE:				1
			DATE:	
CUSTOMER:				1
CONTACT NAME:				
CONTACT NUMBER:				
MAIL ADDRESS:				
SITE ADDRESS:				
SUBURB:				
REQUIRED DATE:				
NOTE: MINIMUM LEAD TII	MES APPLY: PLEASE CHECK	WITH YOUR SALES RE	PRESENTATIVE FOR CC	ONFIRMATION.
AKE OFF TYPE:	QUOTE ONLY	BUILDER APPOIN	TED	OFFICE USE
BUILDERS GROUP:	TAG	NETWORK		
ACCOUNT TYPE:	ACCOUNT	COD	COD TRADE	
TICK FRAME:				COMPLETED
ASSOCIATED MATERIAL:				COMPLETED
PRENAIL FRAME:				COMPLETED
LOOR SYSTEM:				COMPLETED
ROOF TRUSSES:				COMPLETED
ANCILLARIES:				COMPLETED
ARCHITECTURAL:	PROVIDED MUST IN	CLUDE TIMBER SCHED	ULE.	
ENGINEERING:	PROVIDED			
ENGINEERING: SIZING:	AS PER PLANS	AS PER CODE	AS PER ENGINEER	ING
WIND RATING:	N2 / W33	N3 / W41	OTHER	
EXTERNAL STUDS:	450	600		
INTERNAL STUDS:	450	600		
WALL FRAME HEIGHT:	2440	2740	OTHER	
IF LOWER S	TORY WALL EXCEEDS 3M I	N HEIGHT, ENGINEER	ING <u>MUST</u> BE PROVID	ED.
INTERNAL STUDS: WALL FRAME HEIGHT: IF LOWER S FLOOR JOISTS: TRUSSES: DASTERC:	450	600		
TRUSSES:	600	900	1200	
RAFTERS:	600	900	OTHER	
ROOF MATERIAL:	CONCRETE TILES	SHEET METAL	OTHER	
ROOF PITCH:				
DVERHANGS				
REATMENT:	UNTREATED	T2	LOSP H2	
PLEASE NOTE: INSUFFICIENT INFORMA CHARGE). IF P,	TION WILL RESULT IN QUO ARAMETERS ARE OUTSIDE			

NOTES:

BUSINESS FORM ESTIMATION

TAKE OFF REQUEST



STICK WALL FRAME	APPLICABLE			
WIND RATING:	N2 / W33	N3 / W41	OTHER	
TREATMENT:	UNTREATED	T2	LOSP H2	
DOCKED TO LENGTH:	NO	YES		
EXTERNAL STUD CENTRES:	450	600		
INTERNAL STUD CENTRES:	450	600		
POSTS:	HWD	PINE	KWILA LAM	
POST PREFERRED SIZE:				
BEAMS:	HWD	PINE	EWP	
RAFTERS:	CEILING UNDER	CEILING OVER	NIL CEILING	
NOTES:				

NOTE: PARTY WALLS WILL NOT BE QUOTED UNLESS DETAILED ON PLANS. APPLICABLE SPECIFICATION PROVIDED **BRACING & TIE DOWN**

		0. 20. 10. 110		
F22 & BETTER HWD PLY BRACING:				
50 X 38 PINE BATTENS (TEMP):	UNTREATED	LOSP H2		
70 X 35 PINE BATTENS (TEMP):	Т2			
TIE DOWNS:	CHEMSET 101	M12 ANCHO	R BOLTS	
	HOOP IRON	CONCRETE N	AILS	
M12 RODS @ CENTRES:	1200	1350	OTHER	
STUD BOLTS @ CENTRES:	1200	1350	OTHER	
NOTES:				

NOTE: BRACING & TIE	DOWN WILL NOT BE QUO	TED UNLESS DETAILED	ON PLANS.
SOFFITS	APPLICABLE		
50 X 38 BATTENS:	UNTREATED	LOSP H2	70 X 35
F.C. EAVES:	4.5 mm	6.0 mm	
EXTERIOR CEILINGS:	4.5 mm F.C.	6.0 mm F.C.	OTHER
PRE-PRIMED PINE FASCIA:	180 X 25	230 X 31	
NOTES:			
CLADDINGS	APPLICABLE		
AS PER PLANS:			
ALTERNATIVE SPECIFICATION:	HARDIES	HWD	PINE
PROFILE	PLEASE SPECIFY:		
CLADDING ACCESSORIES:	WINDOW TRIMS	TIMBER	HARDIES TO SUIT
	CORNERS	TIMBER	HARDIES TO SUIT
	CORNERS	TIMBER	PINE
BUILDERS PAPER:	WRAP BREATHER	FOIL FIXES	
NOTES:			
FLOORING	APPLICABLE		
3600 X 900 X 19 PBD:	STANDARD	TERMI	YELLOW TONGUE
3600 X 900 X 21 PBD:	RED TONGUE		
TONGUE & GROOVE BOARDS:	HWD	STANDARD	SELECT
19 mm X BOARD WIDTH:	60 mm	86 mm	130 mm
OTHER:	OVERLAY	THICKNESS PLEAS	E SPECIFY:
SCYON INT 2700 X 600 X 19 mm			
DECKING:	86 X 19	90 X 19	130 X 19
	MERBAU	SPOTTED GUM	OTHER
MODWOOD OR SIMILAR:	PLEASE SPECIFY:		
SCYON EXT 2700 X 600 X 19 mm:			

PLEASE SPECIFY:

P: 07 3386 0595

OTHER: NOTES:

E: SALES@5STARTIMBERS.COM.AU



	•		
SALES REPRESENTATIVE:	D/	ATE:	
CUSTOMER:			
SITE ADDRESS:			
SUBURB:			
REQUIRED DATE:			

TRUSSES & PRENAIL FRAMES

TRUSSES	APPLICABLE			OFFICE US
SITE MEASURE REQUIRED:	A COST MAY BE INVOL	VED IF REQUIRED		
WIND RATING:	N2 / W33	N3 / W41	OTHER	
TREATMENT:	T2	LOSP H2	LOSP H3	
ROOF MATERIAL:	CONCRETE TILES	SHEET METAL	OTHER	
CEILING MATERIAL:	10mm P/BOARD	13mm P/BOARD	OTHER	
FIXING METHOD:	DIRECT	ICJ's	BATTENS @	
TRUSS CENTRES:	600	900	1200	
ROOF PITCH:				
OVERHANGS:				
ADDITIONAL LOADS:	AIR CONDITIONER A/C LAYOUT SUPPLIED	PLEASE ADVISE WEI	GHT: KG	
PRENAIL FRAMES	APPLICABLE			
SIZING:	AS PER PLANS	AS PER CODE	AS PER ENGINEERING	
TREATMENT:	T2	LOSP H2	LOSP H3	
EXTERNAL STUD CENTRES:	450	600		
INTERNAL STUD CENTRES:	450	600		

• TRUSS QUOTE: SUPPLY TRUSSES & ALL ANCILLARIES INCLUDING POLE PLATES OR FIXING PLATES.

2440

• PRENAIL & TRUSS QUOTE: SUPPLY ABOVE, PLUS BEAMS TO SUPPORT TRUSSES, FRAME INCLUDING LINTELS, GABLE, BULKHEAD & PARAPET FRAMING INCLUSIVE.

2740

OTHER

• 5 STAR TIMBERS WILL SUPPLY BRACING PLY, POSTS, TIE DOWNS & BEAMS FOR RAFTERS.

• PLEASE NOTE: INSUFFICIENT INFORMATION WILL RESULT IN QUOTATION DELAYS (OR BEING UNABLE TO PROVIDE THIS SERVICE FREE OF CHARGE). IF PARAMETERS ARE OUTSIDE OF AS1684, ENGINEERING MUST BE SUPPLIED.

NOTES:

WALL FRAME HEIGHT:



DATE:

SALES REPRESENTATIVE: CUSTOMER: SITE ADDRESS: SUBURB: REQUIRED DATE:

TIMBER FLOORS, DECKS & ROOF MEMBERS

FLOOR SYSTEM	APPLICABLE		
MEMBER DESIGN:	AS PER PLANS	AS PER CODE	AS PER ENGINEERING
TAKE OFF BY:	DINDAS	5 STAR TIMBERS	
WIND RATING:	N2 / W33	N3 / W41	OTHER
TREATMENT:	T2	LOSP H2	LOSP H3
ROOF MATERIAL:	CONCRETE TILES	SHEET METAL	OTHER
CEILING MATERIAL:	10mm P/BOARD	13mm P/BOARD	OTHER
IXING METHOD:	DIRECT	ICJ's	BATTENS @
OIST CENTRES:	450	600	
MAX. DEFLECTION:	10 mm	OTHER	
END BLOCKING:	SOLID	RIMBOARD	
END JOIST TO BE:	AS JOIST	LVL	
SET DOWNS TO FLOOR:	N/A	WET AREAS:	mm
FLOORING (BY 5 STAR TIMBERS):	PARTICLEBOARD	SCYON	TIMBER OVERLAY
NOTES:			
DECK SYSTEM	APPLICABLE		
DECK TIMBERS:	AS PER PLANS	AS PER CODE	
REATMENT:	UNTREATED	T2	LOSP H3
EARERS:	HWD	EWP	STEEL
LOOR JOISTS:	HWD	EWP	PINE
CEILING UNDER:	NO	YES	
NOTES:			
ROOF RAFTERS	APPLICABLE		
ROOF MEMBERS:	AS PER PLANS	AS PER CODE	
TAKE OFF BY:	DINDAS	5 STAR TIMBERS	
RAFTERS CENTRES:	600	900	OTHER
ROOF PITCH:			
ROOF BEAMS:	EWP	OTHER	
RAFTERS:	EWP	OTHER	
NOTES:			
INSULATED ROOF PANEL	APPLICABLE		
PROFILE:	ORB	TRIM	
ROOF EXTENDA BRACKETS:	(230 – 290) mm	(320 – 380) mm	(420 – 480) mm
NOTES:			



ANCILLARIES

LOCK UP	APPLICABLE					OF	FICE US	SE
ENTRY DOOR:	AS PER PLAN	IS	SPECIAL			RIGHT HAND HINGED DOOR		
SPECIFY STYLE / TYPE:						۱ Þ.,		
REAR DOOR:	XF 1 CLEAR		OTHER			-	ND HINGE	
	1/3 GLASS							DOON
ENTRY FRAME:	PREHUNG		LOOSE JAMBS /	SILL				
	PREPRIMED		HINGED	PI	VOT			
GARAGE JAMBS:	140mm		160mm			DOOR	LH	RH
CAVITY UNITS:	TIMBER		STEEL			520		
BRICK LINTELS:	GALVANISEE)				620		
NOTES:						720		
INTERNAL FITOUT	APPLICABLE					770		
						820		
INTERNAL DOORS						920		
PRIME COAT:								
OAKFIELD 4 PANEL:								
ALTERNATIVE SPECIFICATION:								
CAVITY SLIDER UNITS:								
INTERNAL JAMB								
PREHUNG:	FJ PINE							
LOOSE (JAMB & SILL):	FJ PINE							
ARCHITRAVE								
42 X 11 FJ PINE:	B/NOSE	COL	BEVEL	DAR	3 STEP			
66 X 11 FJ PINE:	B/NOSE	COL	BEVEL	DAR	3 STEP			
ALTERNATIVE SPECIFICATION:								
SKIRTING								
42 X 11 FJ PINE:	B/NOSE	COL	BEVEL	DAR	3 STEP			
66 X 11 FJ PINE:	B/NOSE	COL	BEVEL	DAR	3 STEP			
ALTERNATIVE SPECIFICATION:								
SHELVING								
PARTICLEBOARD:								
MELAMINE:								
SUPPORT FRAME – FJ PINE:	42 X 19		66 X 19					
ASSOCIATED FITOUT								
DOOR FURNITURE:	LEVER		КЛОВ					
FINISH:	CHROME		OTHER					
DOOR HARDWARE:		, CUSHIO	N STOPS, DS01 & D	S02				
ROBE HARDWARE:			AIL ENDS & CENTRE					
NOTES:								



EXTERNAL ANCILLARIES

EXTERNAL FITOUT	APPLICABLE		
BALUSTRADE & STAIRS			
BALUSTRADE:	PRIMED PINE	LAMINATED KWILA	
TOP RAIL:	LADIES WAIST	BREAD LOAF	DAR
BOTTOM RAIL:	DAR	REBATED	
BALUSTRADE:	62 X 19	42 X 42	SPACING:
SS WIRES:	YES	SPACING:	
STRINGERS:	TIMBER	STEEL	
STEP TREADS: 250 X 50:	GOS HARDWOOD	MERBAU / KWILA	
TIMBER SCREENING			
SPECIES:	SPOTTED GUM	MERBAU / KWILA	OTHER
POSTS:	SIZE:	BREAD LOAF	DAR
RAILS:	SIZE:	REBATED	
SCREEN SLATS:	SIZE:	42 X 42 62 X 19	90 X 19
FENCING			
FENCE HEIGHT:			
TIMBER:	HARDWOOD	CCA PINE	
POSTS:	100 X 100	100 X 75	
RAILS - 4.8M:	75 X 38	100 X 38	100 X 50
PALINGS:	75 X 15	100 X 15	
SPACING:	NIL	15mm	
INTES			

NOTES:

I understand that it is my responsibility to check & confirm all materials that are to be quoted. COMPANY NAME: CUSTOMER / CONTACT NAME:

SIGNATURE:

DATE:

5 Star Timbers Confidential Proprietary For Internal Use Only